

KillTest

Higher Quality, Better Service!



Q&A

<http://www.killtest.com>

We offer free update service for one year.

Exam : **300-735**

Title : Automating and
Programming Cisco Security
Solutions (SAUTO)

Version : DME0

- 1.Which description of synchronous calls to an API is true?
- A. They can be used only within single-threaded processes.
 - B. They pause execution and wait for the response.
 - C. They always successfully return within a fixed time.
 - D. They can be used only for small requests.

Answer: B

2.DRAG DROP

Drag and drop the code to complete the script to search Cisco ThreatGRID and return all public submission records associated with cisco.com. Not all options are used.

```
import requests

API_KEY = 'asdf1234asdf1234asdf1234'

QUERY = ' '

URL = 'https://panacea.threatgrid.com/api/v2/ ' / ' '

PARAMS={"q":QUERY,"api_key":API_KEY}

request = requests.get(url=URL, params=PARAMS)

print(request.json)
```

submissions

public

query

cisco

search

cisco.com

Answer:

```
import requests

API_KEY = 'asdf1234asdf1234asdf1234'

QUERY = ' cisco.com '

URL = 'https://panacea.threatgrid.com/api/v2/ search ' / ' submissions '

PARAMS={"q":QUERY,"api_key":API_KEY}

request = requests.get(url=URL, params=PARAMS)

print(request.json)
```

submissions

public

query

cisco

search

cisco.com

Explanation:

Reference:

<https://community.cisco.com/t5/endpoint-security/amp-threat-grid-api/m-p/3538319>

3.Refer to the exhibit.

```
import requests

headers = {
    'Authorization': 'Bearer ' + investigate_api_key
}

domains=["cisco.com", "google.com", "xreddfr.df"]

investigate_url= "https://investigate.api.umbrella.com/domains/categorization/"
values = str(json.dumps(domains))
response = requests.post(investigate_url, data=values, headers=headers)
```

What does the response from the API contain when this code is executed?

- A. error message and status code of 403
- B. newly created domains in Cisco Umbrella Investigate
- C. updated domains in Cisco Umbrella Investigate
- D. status and security details for the domains

Answer: D

4.Refer to the exhibit.

```
import requests

URL = 'https://sma.cisco.com:6080/sma/api/v2.0/quarantine/messages/details?quarantineType=spam&device_type=esa'
HEADERS = {'Authorization': 'Basic Y2h1cGFLYWJSQSZe'}

response = requests.get(URL, headers=HEADERS)
```

A security engineer attempts to query the Cisco Security Management appliance to retrieve details of a specific message.

What must be added to the script to achieve the desired result?

- A. Add message ID information to the URL string as a URI.
- B. Run the script and parse through the returned data to find the desired message.
- C. Add message ID information to the URL string as a parameter.
- D. Add message ID information to the headers.

Answer: C

5.DRAG DROP

Drag and drop the code to complete the API call to query all Cisco Stealthwatch Cloud observations. Not all options are used.

	https://example.observbl.com/api/v3/	
	/	

observations	DELETE	GET
POST	all/	all
obsrv	?query=all	

Answer:

GET	https://example.observbl.com/api/v3/	
observations	/	all

observations	DELETE	GET
POST	all/	all
obsrv	?query=all	