

KillTest

Higher Quality, Better Service!



Q&A

<http://www.killtest.com>

We offer free update service for one year.

Exam : **310-016**

Title : SUN Certified SYSTEM
ADMINISTRATOR FOR
SOLARIS 9,UPGRADE

Version : DEMO

1. Click the Exhibit button. Which type of JumpStart configuration file is shown in the exhibit?

```
install_type    initial_install
system_type     standalone
partitioning    explicit
usedisk         c0t0d0
filesys         c0t0d0s1      128    swap
filesys         c0t0d0s0      free   /
cluster        SUNWCall
```

- A. rules file
- B. class file
- C. finish script
- D. sysidcfg file
- E. bootparams file

Correct: B

2. You believe that you have a correctly configured boot server on the local network for the JumpStart client you are currently attempting to install. Your JumpStart configuration is based on files only and does not use a naming service at any stage. Upon running the command: boot net - install the client repeatedly displays the message: Timeout waiting for ARP/RARP packet What are two possible causes for this? (Choose two.)

- A. The in.rarpd daemon is not running on the boot server.
- B. The sysidcfg file for the client is missing an ether entry.
- C. The client does not exist in the rules.ok file on the boot server.
- D. The /etc/ethers file on the boot server does not have an entry for the client.
- E. The /etc/bootparams file on the boot server has duplicate entries for the client.

Correct: A D

3. Which four JumpStart client items can be configured using the sysidcfg file? (Choose four.)

- A. locale
- B. name service
- C. root password
- D. client host name
- E. patch information
- F. file system layout
- G. software configuration cluster

Correct: A B C D

4. Both NIS and the sysidcfg file are configured to provide JumpStart identification services. Which statement is true?

- A. Only NIS can be used.
- B. Only the sysidcfg file can be used.
- C. Both can be used. NIS takes precedence over the sysidcfg file.
- D. Both can be used. The sysidcfg file takes precedence over NIS.

Correct: D

5. You believe that you have a correctly configured boot server on the local network for the JumpStart client currently being installed. Your JumpStart configuration is based on files only and does not use a naming service at any stage. Upon running the command: boot net - install the

client displays the output: 24000 and subsequently outputs the following text to the console: panic - boot: Could not mount filesystem Program terminated ok What is the cause of this problem?

- A.The root file system is not shared using NFS from the boot server.
- B.The rpc.bootparamd daemon is not running on the boot server.
- C.The installation server is missing the packages SUNWcsu and SUNWcsr.
- D.The class file contains a reference to an NFS mount which is not available.

Correct:A

6.What three tasks must be done on the NIS master to add support for a new JumpStart client? (Choose three.)

- A.re-make NIS maps with the updated client information
- B.edit the hosts file, add the new client name and IP address
- C.edit the ethers file, add the new client name and Ethernet address
- D.edit the bootparams file, add the client name and architecture type
- E.edit the rules file, add the client name and software configuration cluster information
- F.edit the class file, add the client name and location of configuration and installation servers

Correct:A B C

7.Which two commands display the list of patches installed on a Solaris system? (Choose two.)

- A.showrev -p
- B.pkginfo -l
- C.patchadd -p
- D./usr/sbin/prtdiag -v

Correct:A C

8.Which three should you use to obtain patches? (Choose three.)

- A.World Wide Web access
- B.CD-ROM media from Sun
- C.telnet access to SunSolve
- D.anonymous ftp access to the SunSolve ftp site
- E.patch supplied from an official periodical publication

Correct:A B D

9.You want to install a patch cluster on your system to correct several problems. You decide to use the -nosave option to the install_cluster command. Which statement correctly describes the effect of this option?

- A.A log file for each patch is not created.
- B.A log file for install_cluster is not created.
- C.The individual patches cannot be removed if desired.
- D.An entry for the patch in /var/sadm/patch is not created.

Correct:C

10.Given the patch: 111021-01.zip Which command should you use first in a series of steps to install the patch?

- A.patchadd 111021-01
- B.unzip 111021-01.zip
- C.zip -U 111021-01.zip
- D.uncompress 111021-01.zip

Correct:B