

KillTest

Higher Quality, Better Service!



Q&A

<http://www.killtest.com>

We offer free update service for one year.

Exam : **C4090-958**

Title : Enterprise Storage
Technical Support V3

Version : DEMO

1.A customer has just learned that a brand new TS7650G ProtecTIER installation will not run as a virtual tape library with Symantec's NetBackup OST feature concurrently.

When should this implementation situation have been discovered?

- A. The Pre-Sales site survey
- B. The Pre-Install Technical and Delivery Assessment
- C. The Solution Communication Vehicle (PTSCV) spreadsheet
- D. The pre-qualification task performed by the subject matter expert for the disk arrays

Answer: B

2.Which function controls host access to a volume in a switched fabric?

- A. LUN masking
- B. Port masking
- C. Private loops
- D. Buffer to buffer credits

Answer: A

3.A customer has a large non-IBM storage environment, EMO and HDS, with a mixture of VMware, Linux, Unisys mainframe and Windows, including Windows 2003, based hosts. The customer is very interested in XIV storage and the technical specialist has been asked to provide an IBM XIV storage solution with a migration plan to replace his current storage environment.

What is the biggest obstacle to an all IBM solution?

- A. VMware is not supported on XIV
- B. Windows 2003 is not supported on XIV
- C. HDS storage cannot be migrated to XIV
- D. Unisys mainframe is not supported on XIV

Answer: D

4.What is the maximum number of drives supported in a SONAS single array?

- A. 2048
- B. 4096
- C. 7200
- D. 10000

Answer: C

5.A customer with a DS8800 believes that additional host ports need to be connected into the SAN environment.

Which resource or application would be used to determine whether the customer's suspicions are correct?

- A. IBM Tivoli NetCool
- B. Tivoli Storage Productivity Center
- C. Storage Manager Performance Monitor
- D. D58999 Performance Monitoring and Tuning Redbook

Answer: B