

KillTest

Higher Quality, Better Service!



Q&A

<http://www.killtest.com>

We offer free update service for one year.

Exam : E20-357

Title Isilon Solutions Specialist
Exam for Implementation
Engineers

Version : DEMO

1.What is the command to renumber the nodes of the cluster?

- A. Innset
- B. ipset
- C. deliprange / iprange
- D. interface

Answer: A

2.What is the recommended InfiniBand cabling for a dual switch configuration?

- A. Connect the int-a port to the first switch and the int-b port to the second switch.
- B. Connect node 1 int-a into InfiniBand switch port 1, and node 2 int-a into Infiniband switch port 2.
- C. Connect the ext-1 port to the first switch and the int-b port to the second switch.
- D. Connect the ext-1 port to the first switch and the ext-1 port to the second switch.

Answer: A

3.You have just added a node to a cluster. What is the minimum time recommended to wait before adding thenext node?

- A. 5 minutes
- B. 3 minutes
- C. 10 minutes
- D. 20 minutes

Answer: A

4.You have just completed the installation of a cluster. What is a recommended step to check networkconnectivity?

- A. Ping each individual node.
- B. Verify all nodes display in the web administration interface.
- C. Connect to an SMB share and check for file access.
- D. Connect to an NFS export and check for file access.

Answer: A

5.What are the default settings for SupportIQ and remote access?

- A. SupportIQ is enabled; Remote access is disabled
- B. SupportIQ is disabled; Remote access is disabled
- C. SupportIQ is enabled; Remote access is enabled
- D. SupportIQ is disabled; Remote access is enabled

Answer: A

6.A potential customer is considering replacing a four year old, Linux-based NFS server with 40TB of usablecapacity. The existing system supports home directories, an internal website, and a content repository for thecustomer's content management system. The customer is concerned about performance of any new solutionbecause they expect to double workload in the content management system.

- A. syslog and vmstat
- B. Perfmon and sysstat
- C. isi statistics and Wireshark

D. iostat and nfsstat

Answer: D

7. Your customer is moving from a Restaurant/Bar business model to a Restaurant/Casino business model. You are helping architect the upgrade of a current 4-node X200 48 TB Isilon cluster, with 65% utilized for their video surveillance operations. They wish to achieve the following:

Upgrade from 1280 x 720 resolution, with a 15 days retention policy, to 2048 x 1536 resolution with a 30 days retention policy.

What is the minimum number of nodes of the same type will you need to add in order to meet the required changes and not exceed 70% raw capacity?

- A. 6 nodes
- B. 10 nodes
- C. 14 nodes
- D. 18 nodes

Answer: B

8. Your customer is looking for a storage solution that will be able to store seven million three MB files which are rewritten and seldom accessed. Read and write operations are both completed by a web based application, which requires 1.3 Gbps throughput. The customer's network has not been upgraded in many years, so the network interfaces are 1Gbps. Which cluster configuration would best meet the customer's requirements?

- A. 3 NL400 nodes
- B. 3 X400 nodes
- C. 4 X200 nodes
- D. 5 S200 nodes

Answer: C

9. Your customer has a new business unit. They are gathering web log files to be analyzed. They are using Hadoop to do the analysis of the logs. The IT department is centrally storing the log files on a five node Isilon cluster. They have enabled the Hadoop cluster to access the files directly. The nodes are X400's with two SSD drives in each node and 96GB of RAM.

How many DataNodes does the Isilon Cluster have?

- A. 1
- B. 5
- C. 10
- D. 15

Answer: B

10. You have scheduled a meeting with a prospective customer in the Life Sciences vertical market.

Which Isilon features should be presented to them?

- A. SyncIQ, Antivirus, 10 GigE support and HDFS
- B. SmartPools, HDFS, 10 GigE support and SmartQuotas
- C. SmartLock, HDFS, SmartPools and SmartQuotas
- D. SyncIQ, SmartLock, HDFS and SmartConnect

Answer: B

11. An existing customer has two NAS systems providing NFS storage in their main data center - one is an Isilon cluster and the second is an array from another vendor. Both systems are four years old, and the customer would like to consolidate the storage into a single solution.

According to the customer, both systems support identical workloads with similar performance and utilization, and they want the new solution to support 50% performance growth. Which method can model the workload requirements, and what multiplier will capture the requirements for the new solution?

- A. Use isi statistics drives, and multiply by 1.5
- B. Use isi statistics system, and multiply by 3
- C. Use isi statistics protocol, and multiply by 3
- D. Use isi statistics query, and multiply by 2

Answer: B

12. A customer wants to add Unix users to their cluster, and requires that NFS access be fault-tolerant. What would you recommend?

- A. Use NFS v3 and dynamic IP addressing with SmartConnect Basic
- B. Use NFS v4 and dynamic IP addressing with SmartConnect Basic
- C. Use NFS v3 and dynamic IP addressing with SmartConnect Advanced
- D. Use NFS v4 and dynamic IP addressing with SmartConnect Advanced

Answer: C

13. Your customer has an Isilon 4-node X400 cluster used for home directory use, and has since updated to OneFS 7.0. The HR and Legal departments have been very strict about using only dedicated file servers that are part of a single, isolated, untrusted Active Directory domain. Their filer has been out of maintenance, and fears are being raised that, due to the age, it may fail at some point.

What could the IT department do, to allow the HR and Legal groups to provide file share services, with minimal impact to their other application permissions?

- A. Utilize SmartPools to create two pools to separate the domains
- B. Recommend a 2nd cluster for the HR/Legal department
- C. Use Access Zones for each domain
- D. Consolidate onto a single cluster and merge the domains

Answer: C

14. A Media and Entertainment company is considering changing from 2K resolution to 4K resolution. They will continue to use the DNxHD 220 codec.

Assuming everything else stays the same, how will this change affect storage?

- A. Storage will be half as large
- B. Storage will be four times as large
- C. Storage will be twice as large
- D. Storage requirements will not change

Answer: B

15. A customer is looking for a NAS solution to support their read-intensive application. This solution must

meet the following requirements:

- 1000 users
- Aggregate bandwidth of 5 GB/s
- 500 TB of user data
- Typical latency of 5 ms.

The files are distributed evenly across 10 directories. Which cluster configuration would best meet these requirements?

- A. Seven X400 (108 TB) nodes with no SSD
- B. Eight NL400 (96 TB) nodes with 1.6 TB SSD
- C. Eight X400 (96 TB) nodes with 1.6 TB SSD
- D. Twenty-five X200 (30 TB) nodes with 800 GB SSD

Answer: C

16. A NetApp customer is considering Isilon. They use their filers for UNIX home directories, and would like to see a suggested configuration that would meet their needs.

What would you do to help size this cluster?

- A. Use tcpdump and upload the output file to MiTrends to generate a protocol analysis
- B. Ask for an autosupport file and upload it to MiTrends to generate a workflow profile
- C. Ask them to install InsightIQ and collect data from the filer, then import to SQL for analysis
- D. Ask for the output from nfsstat and upload it to MiTrends to generate a workflow profile

Answer: B

17. A customer plans to replace an existing array that is supported by the MiTrend Workload Profile Assessment (WPA) service. You receive performance data from the customer and run a WPA report that shows the array has 50TB of usable capacity. In discussions with the customer, you learn the content is comprised of four million 6MB files and 400 million 64KB files. The customer explains they have a small budget and very limited rack space available in their datacenter. Performance is not a concern because the files are rarely accessed.

Which configuration provides the needed usable capacity using N+2:1 protection, and requires the least amount of rack space?

- A. 3 x NL400 nodes with 2TB Drives
- B. 3 x X400 nodes with 1TB Drives
- C. 5 x X200 nodes with 1TB Drives
- D. 6 x X200 nodes with 1TB Drives

Answer: D

18. Your customer has an existing Isilon cluster with seven X200 nodes. The cluster is used to store home directories and departmental shared folders. They are planning to deploy a new application that generates small block, synchronous writes.

Which OneFS 7 capability can help reduce latency for the new workload?

- A. Prefetcher
- B. Endurant Cache
- C. Solid State Drives
- D. L2 Cache

Answer: B

19. Your customer is a major metropolitan newspaper. Your previous discussion centered on their storage requirements, and you asked them some of the Top Ten questions. They responded: "Well, it's not the prettiest or most high-tech solution...we use Secure FTP (SFTP) to upload the stories and images and put them in a workflow that formats them for printing in the newspaper." "What really worries us is the fact that our StorageArray from your competitor is going out of maintenance in 120 days, and they are dropping support for SecureFTP. This isn't even considered in our D/R Plan. Do you have a better solution with Isilon?" Which Top Ten questions led to this information?

- A. What does your infrastructure look like? What applications access this storage? What protocols and version number?
- B. How much capacity are you looking for? What applications access this storage? What risks are there in your current infrastructure?
- C. What filesystems, SMB, NFS, or other are you using? What does your infrastructure look like? How do you manage your File Systems?
- D. What is your network infrastructure like? How many Storage Fabrics do you have? What is your Disaster Plan for the Newspaper?

Answer: A

20. You are designing a new Isilon cluster that requires backup to tape for all files in the Legal and Accounting shared folders. The customer has sized their IP network to support the application workload, but no additional bandwidth is available.

What should be recommended for the backup solution?

- A. Use Backup Accelerator nodes for 3-way NDMP
- B. Use Backup Accelerator nodes for 2-way NDMP
- C. Use SmartConnect Advanced and 10Gb/s network interfaces with LACP
- D. Use an Avamar NDMP accelerator and dedicated 10Gb/s network interfaces

Answer: B